

ASTEK SILKY PAINT



DESCRIPTION

Silky paint is an interior, water stray, partially glossy, silky and best quality paint.

New: Can be used in food industry production rooms being easily washable according to standards. Wash with detergent and water. vegetable oil, juices, coffee and red wine don't affect the paint.

APPLICATION AREA

Astek Silky paint can be applied on all types of concrete, ordinary lime –cement, cement –lime plasters, BCA, old resistant paintings and gypsum.

APPLICATION

All surfaces must be clean, dry, with no substances which may prevent adhesion. Old and no adhesion paints must be cleaned. Can be colored with ASTEK Coloring system. Can be applied with roller or spraying equipment. After use wash tools with water. Paint must be mixed up very well before use. Can be applied on minimum +5°C degrees temperature for surface and air. Astek Extra Primer must be applied first on very absorbent surfaces. Apply 2 coats.

Attention: It is forbidden to mix up the paint with lime, clay or organic solvents based paints.

DRYING TIME

At + 20°C degrees, 65% relative humidity, 4-6 hours touch drying, 24 hours complete drying.

CONSUMPTION

Aprox: 10 sqm/l. In order to have an exact consumption some tests on the surface must be done.

DILUTION

Dilute with maximum 10% water.

STORAGE

Keep in dry places, safe of frozen and bad weather (min +5°C)

PACKAGING

2,5 l/3,2 kg, 7,5 l/9,5 kg tightly closed buckets.

VALIDITY

36 months starting from manufacture day if packaging and storage conditions are complied with.