

ASTEK DURATEKS



DESCRIPTION

It is an exterior emulsioned textured and acrylic copolymer based paint. It has a matt, structured aspect and it is also ecological and odorless.

APPLICATION AREA

ASTEK DURATEKS can be applied on all types of concrete, on new or with cracks concrete plasters also on previous painted surfaces with emulsioned paints with own adherence. In order to obtain a decorative and structured aspect ASTEK DURATEKS can be applied to cover the fronts making them resistant on strong bad weather. ASTEK DURATEKS can also be applied on interior surfaces to have resistant and highwashable paintings.

APPLICATION

All surfaces must be sound, clean, dry and free of substances preventing adhesion. Wait 2-4 weeks for recently built surfaces to set well. For new, previous painted, dirty or very absorptive surfaces a coat of ASTEKGRUND EXTRA should be applicated. Roller can be used. Do not apply under direct sunlight action or strong wind. Temperature for application is + 5°C for material, surface and air. Clean tools immediately with water after use.

DILLUTION

Ready for use.

CONSUMPTION

Consumption is 500 - 1200 g / sqm. It may vary depending on the support and the structure needed.

DRYING TIME (+ 20 °C, 65%HR)

Thorough drying: 24 hours.

STORAGE

Shelf life of 3 years when stored unopened, in frost free, dry and cool conditions.

PACKAGING

25 kg/ 13,88 l tightly closed recipient