

# ASTEK NARMOTEX 2,5mm



## GROOVED ORNAMENTAL PLASTER

ASTEK MARMOTEX 2,5 mm is a mat, white or colored ornamental structured plaster for inside and outside. It is based on watery stray of acrylic copolymers, pigments and additives.

## PROPERTIES

ASTEK MARMOTEX 2,5 mm is used to decorate and protect outside surfaces made by: concrete, plaster. It can be also used for strong inner paintings. Resistant to strokes, scratches.

## RECOMMENDED SURFACES

It may be applied on: mineral surfaces, concrete, masonry. The surfaces must be dry, smooth, clean, degreased, without lustre or dust. Before application is recommended to apply one coat of ASTEK GRUND RUGOS.

## APPLICATION

After the application of ASTEK GRUND RUGOS white or colored, the plaster is applied in one single coat with non-oxidable tools and the structure is made using plastic tools. It may be colored using the coloring system ASTEK COLORTEK. On large areas is recommended to apply the product without interruption, to prevent material overlap. After use, the tools must be washed immediately by water.

**ATTENTION:** Do not mix the product with: lime, clay or solvent based paint.

## APPLICATION CONDITIONS

Air, support and product temperature: 10-+30°C. Humidity : max. 75%

## DRYING TIME:

Partially drying time: 24 hours; Total drying time: 72 hours

## CONSUMPTION

2,5 - 3 kg/m<sup>2</sup>. It may vary depending on the support and the structure needed.

## DILUTION

It is ready to be used.

## STORAGE

It will be stored in dry, airy spaces, away from frost, in tightly closed recipients. Do not store this product at temperatures below 5C.

## PACKAGING

3 years in tightly closed recipients.

R22 Harmful by inhalation, in contact with skin and if swallowed

S2 Keep out of the reach of children

S7 Keep container tightly closed

S40 To clean the floor and all objects contaminated by this material use water

S47 Kept at temperature not exceeding +30°C

S59 Refer to manufacturer/supplier for information on recovery/ recycling