

ASTEK MARMOSTONE



ASTEK MARMOSTONE is used to decorate and protect outside surfaces made by: concrete, plaster. It can be also used for strong inner paintings. Resistant to strokes, scratches.

RECOMMENDED SURFACES

It may be applied on: mineral surfaces, concrete, masonry. The surfaces must be dry, smooth, clean, degreased, without lustre or dust. Before application is recommended to apply one coat of ASTEK GRUND RUGOS.

APPLICATION

The plaster is applied in one single coat with non-oxidable tools and the structure is made using plastic tools. It may be colored using the coloring system ASTEK COLORTEK. On large areas is recommended to apply the product without interruption, to prevent material overlap. After use, the tools must be washed immediately by water.

ATTENTION: Do not mix the product with: lime, clay or solvent based paint.

APPLICATION CONDITIONS

Air, support and product temperature: 10-30°C.
Humidity : max. 75%

DRYING TIME:

Partially drying time: 24 hours
Total drying time: 72 hours

CONSUMPTION

3,2 – 4,2 kg/m². It may vary depending on the support and the structure needed.

DILUTION

It is ready to be used.

STORAGE

It will be stored in dry, airy spaces, away from frost, in tightly closed recipients. Do not store this product at temperatures below 5C.

PACKAGING

25 Kg buckets

GUARANTEE

36 months from manufacture date following the packaging and storage conditions