

ASTEK HIDROXAN 320



ASTEK HIDROXAN 320

It is a high quality impregnation product. It rejects the water from the surfaces on which is applied

APPLICATION AREA

All types of: concrete, seeming brick, tile.

PROPERTIES

Excellent resistance to water, oil, grease, dirt and chemical agents; steam and gases permeability, easy to lay and clean.

APPLICATION

Surfaces must be dried, cleaned and free of any substances preventing adhesion: greases, salts, algae(weeds), moulds, etc

Brushing or spraying equipment must be used. On very absorbable surfaces is recommended a second layer applied after the moment the first coat was absorbed by the surface. Application on wet surfaces is not allowed. It will be not applied under the following conditions: wind, rain, direct light of the sun rays. Air and surface temperature for application is minimum +5°C and maximum 30°C.

DILUTION

Ready to be used



CONSUMPTION

200-400 ml/m²/coat. Depending on the absorption power of the surface, the consumption may be different.

DRYING TIME (20°C, 65% HR)

Touch drying: 5-6 hours

A higher air humidity and lower temperatures may increase the drying time. Stir up before use.

PACKAGING

Boxes: 3l and 10l

STORAGE

In frost, free, dry and cool conditions.

GUARANTEE

36 months in sealed container