

ASTEK HIDROXAN 321



ASTEK HIDROXAN 321

It is a high quality impregnation product. It rejects the water from the surfaces on which is applied.

APPLICATION AREA

All types of: concrete, seeming brick, sandy stones, paving stones, tile.

PROPERTIES

Excellent resistance to water, oil, grease, dirt and chemical agents, UV rays; steam and gases permeability, easy to lay and clean.

APPLICATION

Surfaces must be dried, cleaned and free of any substances preventing adhesion: greases, salts, algae (weeds), moulds, etc. Brushing or spraying equipment must be used. On very absorbable surfaces is recommended a second layer applied after the moment the first coat was absorbed by the surface. On horizontal surfaces is recommended the application of the third layer. Application on wet surfaces is not allowed. It will be not applied under the following conditions: wind, rain, direct light of the sun rays. Air and surface temperature for application is minimum +5°C and maximum +30°C. After use clean immediately the tools by water.

DILUTION

Ready to be used

CONSUMPTION

200-400 ml/m²/coat. Depending on the absorption power of the surface, the consumption may be different.

DRYING TIME (20°C, 65% HR)

Touch drying: 5-6 hours

A higher air humidity and lower temperatures may increase the drying time. Stir up before use.

PACKAGING

Boxes: 3l and 10l

STORAGE

In frost, free, dry and cool conditions.

GUARANTEE

36 months in sealed container

