

# ASTEK GRUND RUGOS



## DESCRIPTION:

Primer based on dispersion. Composition made of pigments, aditives, binders, filling materials and thin quartz sand.

Can be used as a primer for interior and exterior surfaces on wich will be used ASTEK MARMOTEX and ASTEK MARMOSTONE.

## APPLICATION AREAS:

ASTEK GRUND RUGOS can be used on all surfaces like: lime - cement, cement - lime plasters, gypsum, concrete, thermo insulating facades.

## PROPERTIES:

The product is an adherence structured primer used for an efficient primering of the surfaces, increases the adherence between surface and plaster, protects suface for scratches when plaster is applied.

## PREPARING SURFACES AND APPLICATION:

Surfaces must be with own resistance, clean, dry, free of substances wich prevent adhesion. Can be colored with ASTEK COLORTEK coloring system. Apply with roller in uniform coat. Clean tools immediately with water after use.

## DILUTION:

Depending on the application can be diluted with max. 10 % water.

## DRYING TIME:

At +20°C, 65 % humidity:

Drying through: 12 hours.

## CONSUMPTION:

8,3 mp / 1 L. In order to have an exact consumption tests must be done on the surface.

## PACKING:

2,4 / 4 kg, 6 l / 10 kg tightly closed buckets.

## STORAGE:

Keep in dry places, safe of frozen and bad weather ( min.+5°C ).

## VALIDITY:

36 months starting from manufacture day if packaging and storage conditions are complied with.