

ASTEK RETUS

ADHESIVE FOR CERAMIC TILES



1 DESCRIPTION

Adhesive resins in water dispersion, various additives and controlled grain marble, is in the form a paste, ready for use, this adhesive works very easily because it has a great time there machinability and material losses.

2. Classification according to EN 12 004

Is a dispersion adhesive (D), normal-dry (1), thixotropic, without sliding (T), the adhesive open time, extended (E) Class D1TE

3. SCOPE OF APPLICATION

It used to work tile and sandstone cladding for interior, surfaces of concrete, gypsum plaster, lime and cement, gypsum, brick, old paint (dispersion) resistant, etc..

4. WORKING SURFACE PREPARATION

Support surface on which the adhesive must be clean, with its resistance, dry, without fissures or cracks, adhesion and compact, free of grease, dust, waste of flour and salts. Old deteriorated mortar (which shows swelling, scorjiri) is removed.

5. APPLICATION

Before using the product mix it to obtain a homogeneous mixture, easily processed. Apply adhesive directly to hard tooth trowel. To choose suitable trowel that will follow behind ceramic tiles to be coated with adhesive paste on most of its surface. Open time (adhesive spread on the support) in normal conditions of temperature and humidity is 40-50 minutes so the boards will be mounted in time, and adhesive surfaces may be stretched more than approx. 4MP. Immediately after use, clean tools with water.

6. TECHNICAL SPECIFICATIONS

Appearance: Viscous paste, homogeneous

Color: White

Density: 1.65 + / - 0.05 g / ml

Application temperature: from +5 ° C to 30 ° C

Adhesive open time: 40-50 min.

7. Stand Before use

Surfaces can be applied after approx. 8-10 days depending mounting support water absorption.

8. CONSUMPTION

Approx. 1.5 to 3.0 kg / m depending on the size spatula needle teeth and the kind support, a consumer will determine just after performing a test.

9. PACKAGING AND STORAGE

Container: 1 kg / 0.6 L, 4 kg / 2.4 l 12 kg / 7.3 l sealed, the stored in areas protected from frost and weather (at least +5 ° C to +30 ° C)

10. VALIDITY

15 months from manufacturing date, under the provision of packaging and storage

11. RECOMMENDATIONS

a. The adhesive should not be used in the following cases:

- Outdoor applications or in areas with continuous immersion (swimming pools, etc.).
- Mounting plate absorbing absorbing media
- Installation of decorative tiles from natural stone (eg marble)

b. During application which should stay applied adhesive has formed a hard crust of loose skin to reach with hands and if there is still fresh. In case this film was formed, try to span again the adhesive with spatula teeth.

c. Do not wet tiles with water before application, if you are very dusty, clean with clean water quickly

d. Plates are normally applied by hand pressing them so as to achieve an optimum contact with the adhesive

e. Time correction (in which tiles can be repositioned) is max. 50 min.

f. Mounted with adhesive finishes must not be subjected to washes in the first 10 to 12 days after the opera

12. SAFETY PHRASES

S2 Keep out of reach of children

S7 Keep container tightly closed

S40 to clean soil or soiled articles of this product
water use

S29 Do not empty into drains

S47 Do not store at a lower temperature of +5°C and not exceeds +30°C

S59 Please contact the manufacturer for information on recovery / recycling of packages