



www.asteck.com.ro

ASTEK RETUS

Joint paste ceramic tiles

1. DESCRIPTION

Resin-based paste in water dispersion, additives, fillers in paste form, ready for use.

2. AREAS OF USE

It is used in grouting tiles and wall tiles for interior.

3. SURFACE PREPARATION AND APPLICATION SUPPORT

The correct application will observe the following steps:

1. Before applying the adhesive paste which was made plating should be well dried.
2. Joints must be clean, dry, without chemicals could prevent adhesion, joints must be continuous in the vertical-section and hold until the adhesive paste to penetrate.
3. Before using the product, mix it to obtain a homogeneous mixture, easily processed. Applying the paste is made with special tools (tool with sponge or rubber spatula) loading joints well with the paste, making sure that the application be uniform, not to leave spaces empty between joints, remove excess material shall immediately with a cloth or sponge. The maximum dimension for the space between tiles not exceed 3 mm.
4. Dressing (shaping) can make joints when the paste begins to dry, a damp sponge or with a cloth. Trimming time is chosen depending on the type of application (Absorbent or less absorbent) and operating temperature to avoid removing pulp of heart or strengthening its surface plates. Samples is recommended. After strengthening enough pulp of joint surfaces are cleaned with water. During finish will not require mechanical pulp (eg scratching). After use, clean tools with water immediately.

4. TECHNICAL SPECIFICATIONS

Appearance: viscous paste, homogeneous

Color: white or colored with dyes ASTEK system

Density: 1.6 + / - 0.05 g / ml

Application temperature: between +5 ° C and +30 ° C

Drying time: 24-48 hours, in other conditions of temperature and moisture is likely to dry more slowly or faster.

5. CONSUMPTION

Approx. 0.3 -0.8 kg / m, it varies depending on the size and shape of plates, width and depth of the joints, loss of material application.

7. PACKAGING AND STORAGE

1kg container / 0.62 l 4kg / 2.5 l sealed, are stored in places protected from frost and weather (temperatures between +5 ° C and +30 ° C)

8. VALIDITY

36 months from manufacturing date, under the provision packaging and storage

9. RECOMMENDATIONS

The product must be protected from water temperatures below +5 ° C until he is fully hardened and dried.

During the first 10 days after application joints will be cleaned only with clean water, no other cleanser.

To help avoid stains of color (if colored paste), which were glued adhesive sheets will be completely dry.

The product is recommended for joints that are permanently under water (eg ponds, pools). If the porous plate surface, wipe it immediately with a cloth to avoid staining them.

10. SAFETY PHRASES

S2 Keep out of reach of children

S7 Keep container tightly closed

S40 To clean soil or soiled articles of this product water use

S29 Do not empty into drains

S47 Do not store at a lower temperature of + 5 ° C and not exceeding +30 ° C

S59, please contact the manufacturer for information on recovery / recycling packaging