



ASTEK FINISHING INTERIOR PASTE

1. DESCRIPTION

Product-based resins in water dispersion, paste form, ready to use, with a consistent creamy, smooth, with very good adhesion. With the paste work is very easy because they have a great time there machinability and material losses.

2. SCOPE OF USE

Recommended for leveling and smoothing interior surfaces before painting, such as plaster on limestone, lime, cement, concrete surfaces, gypsum boards, etc..

Surfaces must meet the following conditions:

- Be flat and smooth
- With its adherence (new surfaces have a length of min. 28 days)
- Clean - no dust, free a release substances (grease, bitumen, old paint, etc.).
- No major cracks (larger than 0.3 to 0.5 mm) that can lead to cracking plaster after drying
- Heavy, stable, compact
- Dry Well
- ASTEK PRIMER EXTRA must be apply.

3. APPLICATION

Before using the product mix it to obtain a homogeneous mixture, easily processed. Apply uniform paste with trowel. The material can be drawn into a thick layer of 1-2 mm. If you require support a greater load is recommended to apply the product in two layers. In applying successive layers must be considered to be well above that layer dry and harsh (is polished with abrasive paper fine). After drying the last layer of paste polish with abrasive paper fine to obtain perfect surfaces, smooth, thus removing any imperfections caused by defects in flatness of the application. Immediately after the general tools to clean water.

4. TECHNICAL SPECIFICATIONS

Density: 1.65 + / - 0.05 g / ml

Appearance: viscous paste, homogeneous

Color: White

Featured layers: 1-2 layers depending on the support (or absorbent porous)
Is ready to use.

Drying time: at 20 ° C and relative humidity 65%, 3-6 hours depending on thickness, low temperatures and high humidity increase the drying time.

5. CONSUMPTION

approx. 0.4 to 0.6 kg / m / layer. Real consumption will be determinated by making

some tests directly on support that is to be finished.

6. PACKAGING AND STORAGE

Recipient: 4kg / 2.4 l 25 kg / 15 l sealed and protected by frost and weathering (+5 ° C and 30 ° C)

7. VALIDITY

36 months in terms of compliance with packaging and storage

8. TIPS

1. The first painting will only apply on paste completely dry and primed with ASTEK PRIMER EXTRA.
2. Do not apply in direct sunlight in the presence of strong air currents, or temperatures below +5° C higher than +30 ° C
3. Not be thicker layers of 1-2 mm, otherwise there is possibility to the crack layer

SAFETY PHRASES

S2 Keep out of reach of children

S7 Keep container tightly closed

Cleaner S40 soil or soiled articles of this product
water use

S29 Do not empty into drains

S47 Do not store at a lower temperature +5° C and not exceeding +30 ° C

S59 Please contact the manufacturer for information on recovery / recycling
packaging