

ASTEK MARMOSIL



ASTEK MARMOSIL 2 mm - Grooved Silicon Ornamental Plaster

PROPERTIES

ASTEK MARMOSIL 2 mm is used to decorate and protect outside surfaces made by: concrete, plaster. It can be also used for strong inner paintings. Resistant to strokes, scratches. ASTEK MARMOSIL 2 MM is a grooved silicon ornamental plaster with autocleaning effect.

RECOMMENDED SURFACES

It may be applied on: mineral surfaces, concrete, masonry. The surfaces must be dry, smooth, clean, degreased, without lustre or dust. Before application is recommended to apply one coat of ASTEK GRUND RUGOS.

APPLICATION

After the application of ASTEK GRUND RUGOS white or colored, the plaster is applied in one single coat with non-oxidable tools and the structure is made using plastic tools. It may be colored using the coloring system ASTEK. On large areas is recommended to apply the product without interruption, to prevent material overlap. After use, the tools must be washed immediately by water.

ATTENTION: Do not mix the product with: lime, clay or solvent based paint.

APPLICATION CONDITIONS

Air, support and product temperature: 10-30° C

Humidity : max. 75%

DRYING TIME:

Partially drying time: 24 hours

Total drying time: 72 hours

CONSUMPTION

2 - 2,5 kg/m². It may vary depending on the support and the structure needed.

DILUTION

It is ready to be used.

STORAGE

It will be stored in dry, airy spaces, away from frost, in tightly closed recipients. Do not store this product at temperatures below 5°C.

PACKAGING

Bucket : 25 kg / 14 l. 3 years in tightly closed recipients.

R 22 - Harmfull by inhalation, in contact with skin and if swallowed.

S 2 - Keep out of the reach of the children.

S 7 - Keep container tightly closed.

S 29 - Do not empty into drains.

S 40 - To clean the floor and all objects contaminated by this material use water.

S 47 - Keep at temperature + 5°C - +30°C.

S 59 - Refer to the manufacturer for information on recovery / recycling.