

ASTEK SILTEX



DESCRIPTION

ASTEK SILTEX is an emulsion acrylic resin with added silicone, superelastic, textured.

PROPERTIES

The product is used in construction ASTEK SILTEX for protection and decoration of exterior surfaces of concrete, plaster, masonry, etc.. Do not allow water retention area that has been applied. Due to its silicone composition allows cleaning facades. It can be used for painting interior and superwashable resistant. It is recommended that the surface to be primed with ASTEK GRUND SILICONIC. Apply the product 6 hours later after priming with primer.

SUBSTRATE PREPARATION AND APPLICATION

Apply to exterior surfaces of cement, plaster, concrete and any type of thermal leisure.

Surfaces must be dry, clean, smooth, strong and primed in advance.

From an aesthetic point of view, we recommend applying a surface (wall) at once, without interruption. To avoid shading recommend using the same batch of product.

Before using the product mix.

ASTEK SILTEX can be applied by roller or roller coat the sponge with holes to get different models, with movements up and down, and how the product is wet.

Roller must be dry and clean. Fur roller can be used to obtain different models.

In case of wind or sunlight to prevent rapid drying can add water.

WARNING! It is forbidden to mix the product with: lime, clay or organic solvent-based paints.

CONDITIONS OF USE

Average temperature: 10-30 ° C

Relative humidity: max. 75%

Substrate temperature: 10-30 ° C

Product temperature: 10-30 ° C

DRYING TIME Between 6 to 24 hours.

CONSUMPTION

This can vary depending on the nature of the support, structure desired and skill of applicator, the guide 1 - 1.5 kg / sqm. An exact consumption will be determined after performing a test.

DILUTION

It is ready to be used.

STORAGE

It will be stored in dry, airy spaces, away from frost, in tightly closed recipients. Do not store this product at temperatures below 5°C.

PACKAGING

Bucket : 25 kg / 14 l. 3 years in tightly closed recipients.

R 22 - Harmfull by inhalation, in contact with skin and if swallowed.

S 2 - Keep out of the reach of the children.

S 7 - Keep container tightly closed.

S 29 - Do not empty into drains.

S 40 - To clean the floor and all objects contaminated by this material use water.

S 47 - Keep at temperature + 5°C - +30°C.

S 59 - Refer to the manufacturer for information on recovery / recycling.